What is claimed is:

4

A golf club shaft comprising:

an elongated tubular shaft comprising a plurality of layers of fibers imbedded in a synthetic resin, said elongated tubular shaft having a butt end of relatively

larger cross sectional diameter tapering without intervening discontinuities to a tip end of

relatively smaller diameter, said tip end having an outside diameter adapted to be attached

to a club head; 6

said butt end having an outside diameter no greater than .560 inches. 7

The golf club shaft of claim 1, wherein: 1 2.

said butt end has an outside diameter of from .400 to .560 inches.

The first own to be the first own the first

2

5

The golf club shaft of claim 1, wherein: 3.

said butt end has an outside diameter of from .520 to .540 inches.

2

3

The state of

the golf club shaft of claim 1, further comprising: 4.

galf klab/grip having a standard outside contour and having an inside

diameter of from .400 to .560 inches.

5. 1 The composite golf club shaft of claim 1, further comprising:

2 two inner layers of graphite fibers imbedded in epoxy, said inner layers

having fibers oriented at angles of +45° and -45° respectively relative to the axis of the 3

shaft. 4

1

6. The composite golf club shaft of claim 1, further comprising:

2 an intermediate layer of graphite fibers embedded in epoxy, said graphite

fibers being oriented longitudinal to the axis of the shaft. 3

	1	7. A composite golf club shaft comprising:
	2	an elongated tubular shaft comprising a plurality of layers of fibers
1	3	imbedded in a synthetic resin, said elongated tubular shaft having a butt end comprising a
7/	4	substantially cylindrical cross section of relatively larger cross section, which transitions
X2/	5	without intervening discontinuities to a tapered intermediate section, said tapered
./	6	intermediate section tapering without intervening discontinuities to a relatively smaller
	7	diameter tip end, said tip end having an outside diameter adapted to be fitted to the hosel
	8	of a club head;
•	9	said butt end having as outside diameter no greater than .560 inches.
•	1	8. The golf club shaft of claim 7, wherein:
	2	said butt end has an outside diameter of from .400 to .560 inches.
	,	bul D3/
	1	9. The golf club shaft of claim 7, wherein:
	2	said butt end has an outside diameter of from .520 to .540 inches.

ľ.	1	10. The golf club shaft of claim 7, further comprising:
	2	a golf club grip having a standard outside contour and having an inside
	3	diameter of from .400 to .560 inches.
4	1	11. The composite golf club shaft of claim 7, further comprising:
	2	two inner layers of graphite fibers imbedded in epoxy, said inner layers
	3	having fibers oriented at angles of +45° and -45° respectively relative to the axis of the
	4	shaft.
	1	12. The composite golf club shaft of claim 7, further comprising:
	2	an intermediate layer of graphite fibers embedded in epoxy, said graphite
	3	fibers being oriented longitudinal to the axis of the shaft.